

Sortimentsübersicht 3-Schicht Platten Fichte

Verleimung: AW 100, Leimfuge hell
 Oberfläche: beids. Geschliffen
 Eigenschaften: SWP/2 tragend (teilw. SWP/2 SD)
 Holzfeuchte ab Werk: 8% (teilw. 10%) +/- 2%
 Lieferfrist: ca. 1-3 Arbeitstage
 andere Formate: auf Anfrage

Qualität	Länge Dicke Breite	3000 1250	5000 1025	5000 1250	5000 2050	5000 2500	6000 1250	6000 2070	6000 2500
A/B	15			35					
	19			25	25				
	27			20					
	42				12				
	60				10				
AB/B AB/C	13				40				
	19			25	25				
	27				20				
	42		10						
B/C	13				37				
	16		30		30				
	19	25	25	25	25				15
	21		20		20				
	22				25				
	27	20	20	20	20	20	18	20	20
	34					15			15
	35			15	15				
	42		12	12	12	12			12
	45				11	q			
	60				8	8 (l + q)			8
80								5	
100								5	
C+/C+	19	25	25	25	25	25			
	27	20	20	20	20		18		
	30				15				
	34			15	15				
	42		12	12	12				
	60				8				
C+/C	27			20	20	20		20	20
	35					15			15
	42					12			12
	60								8
C+/D	19		25	25	25				
	27		20	20	20		18		18
	42		12		12				
	60				8				
	80								5
	100								5
D/D	27		20	20	20				18
	42				12				